

elcometer®
inspection equipment



Elcometer 508
Push Off Adhesion Tester

Elcometer 508

Digital Push Off Adhesion Tester

STANDARDS:
ASTM D 4541, ISO 16276-1,
NF T30-606

The Elcometer 508 Push Off Adhesion Tester is an extremely versatile Type III* adhesion gauge which can be used for many adhesion testing requirements. Tests can be made on flat or curved (concave and convex) surfaces.

Hand-held, ergonomic and fully portable - ideal for on-site adhesion testing

Measurement range up to 25MPa (3630psi) with a full scale accuracy of $\pm 1.5\%$

Quick connect coupling for easy connection to the dolly

Rotating crank handle applies smooth loading from 0 up to 25MPa (3630psi)

new



Digital Push Off Adhesion Tester

Elcometer 508

Standard, convex and concave dollies can be used with the Elcometer 508, ideal for testing the adhesion of coatings on flat or curved surfaces such as pipelines and tanks.

Powerful

- Suitable for use on flat, concave & convex surfaces
- Rugged & lightweight
- Smooth load application up to 25MPa (3630psi)

Durable

- Sealed, heavy duty & impact resistant
- Dust & waterproof equivalent to IP65
- Suitable for use in harsh environments

Flexible

- Easy to use hand-held design
- Ideal for field use on tanks & pipelines
- Reusable stainless steel dollies
- MPa / psi switchable

Accurate

- Measurement range up to 25MPa (3630psi)
- Full scale accuracy of $\pm 1.5\%$
- Maximum hold - displays the highest value reached

new



The rubber protected backlit digital LCD displays the reading in MPa or psi. Maximum hold feature displays the highest value reached.



Flexible cable design allows the coupling to be positioned easily over the dolly. The pin is pushed through the centre against the substrate providing accurate repeatable results.



Supplied in a robust plastic carry case the kit includes the Elcometer 508 and five dollies which can be cleaned with the supplied heated tongs and reused.

*Type III in accordance with ASTM D 4541

Adhesion - Push Off

Elcometer 508

Digital Push Off Adhesion Tester

Technical Specification

Part Number	Description	Certificate
UK 240V/EUR 220V	US 110V	
F508-DD	F508-DC	Elcometer 508 Digital Push Off Adhesion Tester
Dolly Size	Outside Diameter	19.4mm (0.76")
	Inside Diameter	3.7mm (0.15")
	Area	284mm ² (0.44sq.inch)
Scale Range	0 - 26MPa (0-3800psi)	
Operating Range	2 - 25MPa (290 - 3630psi)	
Scale Resolution	0.01MPa (1psi)	
Accuracy	±1.5% of full scale	
Power Supply	2 x AA alkaline dry batteries (rechargeable batteries can be used)	
Weight	Gauge: 1.7kg (3.7lb)	Kit: 4.5kg (9.9lb)
Instrument Length	290mm (11.5")	Coupling Height: 200mm (8")
Packing List	Elcometer 508, transit case, 5 flat dollies, 5 dolly plugs, MC1500 quick curing adhesive, dolly cleaning tool, heating tongs, 2 x LR6 (AA batteries), operating instructions and calibration certificate	

Accessories

Part Number	Description	Part Number	Description
T9999646-	Standard Flat Dolly (x1)	-	Concave & Convex Dollies available upon request
T99911135	Cyanoacrylate Adhesive	T9994586-	Dolly Cleaning Tool
T99911136	Dolly Plug (x5)	T99923147	Dolly Cleaning Heating Tongs - EUR 220V / UK 240V
T99914009	Dolly Cutter	T99923103	Dolly Cleaning Heating Tongs - US 110V

● Calibration Certificate supplied as standard.

The Elcometer 508 is supplied with a 1 year warranty as standard, extendable to 2 years, free of charge, via www.elcometer.com

ENGLAND

Elcometer Limited
Manchester M43 6BU
Tel: +44 (0)161 371 6000
Fax: +44 (0)161 371 6010
e-mail: sales@elcometer.com

GERMANY

Elcometer Instruments GmbH
D-73431 Aalen
Tel: +49(0)7361 52806 0
Fax: +49(0)7361 52806 77
e-mail: de_info@elcometer.de

REPUBLIC OF SINGAPORE

Elcometer (Asia) Pte Ltd
Singapore 589472,
Tel: +65 6462 2822
Fax: +65 6462 2860
e-mail: asia@elcometer.com

BELGIUM

Elcometer SA
B-4681 Hermalle /s Argenteau
Tel: +32 (0)4 379 96 10
Fax: +32 (0)4 374 06 03
e-mail: be_info@elcometer.com

THE NETHERLANDS

Elcometer NL
Euclideslaan 251
3584 BV Utrecht
Tel: +31 (0)30 210.7005
Fax: +31 (0)30 210.6666
email: nl_info@elcometer.com

USA

MICHIGAN
Elcometer Inc
Rochester Hills Michigan 48309
Tel: +1 248 650 0500
Toll Free: 800 521 0635
Fax: +1 248 650 0501
e-mail: inc@elcometer.com

FRANCE

Elcometer Sarl
45380 La Chapelle-Saint-Mesmin
Tel: +33 (0)2 38 86 33 44
Fax: +33 (0)2 38 91 37 66
e-mail: fr_info@elcometer.com

JAPAN

Elcometer KK
Nisso Dai 23 Building,
Room 804, 3-8-25, Toranomon,
Minato-ku, Tokyo 105-0001
Tel: +81-3-6869-0770
Fax: +81-3-6809-1442
e-mail: jp_info@elcometer.com

USA

TEXAS
Elcometer of Houston
1146 Sheffield, Unit D,
Houston, TX 77015
Tel: +1 713 450 0631
Toll Free: 800 521 0635
Fax: +1 713 450 0632
e-mail: inc@elcometer.com

www.elcometer.com