

RS20 Rotating System


Reliable quality assurance for your semi-finished products



• rugged, compact, affordable

Reliable semi-finished product testing

System configuration



Production speed vs. defect length

Order no.	RPM	# probes / track width (mm)	complete surface testing	non-complete surface testing						
LAB 6715ND	12 000	2/3,6	min. defect length (mm)							
			7,2	8	9	10	12	15	20	30
			max. production speed (m/s)							
			1,44	1,76	2,16	2,56	3,36	4,56	6,56	10.56
LAB 6717ND	12000	2/1,8	min. defect length (mm)							
			3,6	5	8	9	10	12	15	20
			max. production speed (m/s)							
			0,72	1,28	2,48	2,88	3,25	4,08	5,28	7,28

Production speed (m/s) = RPM x number of probes x (min. defect length (mm) – track width (mm))/60000

Technical data

Application

- Offline, inline, continuous
- Any application in which longitudinal surface flaws are
- Wire, bar, pipe
- All metals
- ▶ Size range: Ø 2–20 mm (0.079"–0.787"): complete diameter change within max. 5 minutes
- ▶ Temperature of inspected material: 0-70°C (32-160°F)

Production line

- Continuous production with/ without cut-off (e.g. drawing line)
- Testing of cut lengths (inline and offline)

Defect resolution

- Min. defect length: depends on production speed and probe (see table above)
- Min. def. depth: 0.05 mm (0.002") dep. on surface conditions

Probe disks

- 2 differential probes & 1 lift-off probe per disk
- ▶ Every probe diameter available

Guidance system

- Internal, with bushings and carbide inserts
- External guidance system recommended

Spindle bearings

Hybrid bearings (ATCoat coated) with a long service life

Revolutions per minute

12 000 rpm

Motor and power supply

- Three-phase asynchronous drive
- 3-phase, 400 V, 50/60 Hz; max. power rating: 370 VA

Eddy current instrument


▶ EDDYCHEK®5


Weights

- Rotating system 40 kg (88 lb)
- Switch cabinet 17.4kg (38.3lb)

Dimensions

see below





© Copyright 2015 by PRÜFTECHNIKAG. ISO 9001:2008 certified. EDDYCHEK® is a registered trademark of PRÜFTECHNIK Dieter Busch AG. No copying or reproduction of this information, in any form whatsoever, may be undertaken without express written permission of PRÜFTECHNIK AG. The information contained in this leaflet is subject to change without further notice due to the PRÜFTECHNIK policy of continuous product development. PRÜFTECHNIK policy of continuous product development. PRÜFTECHNIK policy of continuous product development. products are the subject of patents granted or pending throughout the world



- ► Global Presence
- ► Qualified Support
- **Quality Service**



PRÜFTECHNIK NDT GmbH Am Lenzenfleck 21 85737 Ismaning Germany

www.ndt.pruftechnik.com Tel.: +49 89 99616-360

Fax: +49 89 967990

E-Mail: ndt-sales@pruftechnik.com

A member of the PRÜFTECHNIK group