

Elcometer 3540 Four Sided Film Applicator

The Elcometer 3540 Four Sided Film Applicators are easy to clean gauges manufactured to the highest accuracy.

These precision ground stainless steel Four Sided Film Applicators have 4 thicknesses per applicator each with a flat edged prismatic body making them suitable for coatings applied to a flat and relatively strong substrate.

Available in a range of film widths and can be used with the Elcometer 4340 Motorised Film Applicators.



STANDARDS:
ASTM D 823-E

Technical Specification C

Part Number		Model	Film Thickness		Film Width ⁺		Certificate
Metric	Imperial		µm	mils	mm	inches	
K0003540M001C	K0US3540M001	Elcometer 3540/1	50, 100, 150, 200	2, 4, 6, 8	50	2	o
K0003540M002C	K0US3540M002	Elcometer 3540/2	50, 100, 150, 200	2, 4, 6, 8	75	3	o
K0003540M003C	K0US3540M003	Elcometer 3540/3	50, 100, 150, 200	2, 4, 6, 8	100	4	o
K0003540M004C	K0US3540M004	Elcometer 3540/4	50, 100, 150, 200	2, 4, 6, 8	150	6	o
K0003540M005C	K0US3540M005	Elcometer 3540/5	50, 100, 150, 200	2, 4, 6, 8	200	8	o
K0003540M006C	K0US3540M006	Elcometer 3540/6	50, 100, 150, 200	2, 4, 6, 8	250	10	o

Can be used with the Elcometer 4340 Motorised Film Applicator

